



Vinyl Tapes for Floor and Hazard Marking

MRO
Essentials



*Adhere on contact, resist wear and spills,
and remove cleanly when you're ready*

When you want easy product solutions for marking, identifying, and color-coding, depend on 3M™ vinyl tapes for application simplicity and durability.

- 3M pressure sensitive rubber adhesive sticks on contact to just about any surface for fast application with no dripping, drying, or clean-up.
- Durable vinyl backing resists abrasion, scuffing, moisture, weathering, acids, and alkaline chemicals for long service life.

- Bright colors are locked into the vinyl for permanent high visibility. Select from nine colors or transparent to let underlying color show through.
- Flexible construction stretches and conforms to curved surfaces and around corners for a tight fit.
- When you're ready, 3M Vinyl Tapes peel up easily and leave no adhesive behind.

Application Ideas

- Marking lanes and corridors in factories, warehouses, and hospitals

- Marking hazardous or no-go areas
- Highlighting safety equipment protruding equipment, or low hanging objects
- Delineating playing areas and out-of-bounds in sports facilities
- Color-coding instruments, storage systems, and piping
- Decorative marking

3M™ Vinyl Tapes

Product/ Color	UPC # 021200-	Size	Tape Structure (Backing/ Adhesive)	Backing Thickness mils (mm)	Total Thickness mils (mm) (N/100 mm)	Adhesion to Steel oz/in. (N/100 mm)	Tensile Strength lbs./in. (N/100 mm)	Elongation at Break %	Temperature Range °F (°C)	Packaging
ASTM Test Method:				D-3652	D-3652	D-3330	D-3759	D-3759		
Premium performance Vinyl Tape										
471/Black	04306-2	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/Blue	04308-6	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/Green	04313-0	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/Orange	04312-3	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/Red	04305-5	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/Trans.	04314-7	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/White	04311-6	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
471/White	06466-1	3 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	12 per case
471/Yellow	04310-9	2 in. x 36 yds.	Vinyl/Rubber	4.1 (0.10)	5.2 (0.13)	23 (25)	16 (280)	130	40 to 170 °F (4 to 77°C)	24 per case
3M™ Safety Stripe Tapes										
5700/Black & White Stripes	04367-3	2 in. x 36 yds.	Vinyl/Rubber	4.2 (0.11)	5.5 (0.14)	19 (21)	15 (260)	170	40 to 170 °F	24 per case
5700/Black & White Stripes	03954-6	3 in. x 36 yds.	Vinyl/Rubber	4.2 (0.11)	5.5 (0.14)	19 (21)	15 (260)	170	40 to 170 °F	12 per case
5702/Black & Yellow Stripes	03951-5	3 in. x 36 yds.	Vinyl/Rubber	4.2 (0.11)	5.4 (0.14)	19 (21)	15 (260)	170	40 to 170 °F	12 per case
5702/Black & Yellow Stripes	04585-1	2 in. x 36 yds.	Vinyl/Rubber	4.2 (0.11)	5.4 (0.14)	19 (21)	15 (260)	170	40 to 170 °F	24 per case

NOTE: The technical information and data provided above is a general guide only and should be considered representative or typical only and should not be used for specification purposes.

MRO Essentials— You could browse through the thousands of products at 3M to find time and work saving solutions for MRO tasks and problems. Or you could make one call to **1-800-362-3550** or go to the one site that focuses specifically on your needs. From abrasives to adhesives, masking tape to ear plugs, electrical connectors to cleaning products, simply click...

www.3M.com/industrial

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Business

Customer Response Center
900 Bush Avenue, Building 21-1W-10
St. Paul, MN 55144-1000



Minimum 10% Post-Consumable Fiber

3M is a trademark of 3M

Printed in U.S.A.
© 3M 2004 78-6901-2105-4